




RCU series fiberglass commercial filter is made of high quality fiberglass and resin , the fiberglass winding structure makes the sand filter more stronger , there ' s UV - resistant on the surface , the whole filter has good resistance to chemical and sun protection . The Useries fiberglass commercial filter is the first choice for water treatment equipment at swimming pools spas , fountains , aquariums , water parks & etc.



- RCU resistant surface finished .
- Designed to assemble with butterfly valve .
- Max . operating pressure 36 psi (2.5 bar) or 56 psi (4.0 bar) is optional .
- Max . temperature of 43 ° C (109 F)
- Suggested size of media : 0.5-0.8mm sand and 2-1mm gravel

Optional accessories :

Filtration system : Laterals / Nozzles Others : Sight glass / Manhole / 33mm union drain / Air purge

Kodu Code	Maksimum akış hızı Max flow rate		Filtre Alanı Filter area m ²	Liman Boyutu Port size		Kum Sand		Boyutlar Dimensions(mm)		
	Lpm	m ³ / h		inch	mm	0.5-0.8 mm	1-2mm	A	B	C
RCU1200	860	52	1.13	"3	90	900	300	1450	1200	900
RCU1400	1150	69	1.54	"4	110	1350	450	1650	1400	1000
RCU1600	1500	80	2.00	"4	110	2300	700	1800	1600	1100
RCU1800	2000	125	2.70	"6	160	2900	900	1900	1800	1300
RCU2000	2350	157	3.14	"6	160	4000	1100	2150	2000	1350
RCU2300	3440	217	4.30	"8	200	6000	1600	2350	2300	1500
RCU2500	3920	250	4.90	"10	250	6700	1800	2650	2500	1600
RCU3000	5883	353	7.07	"10	250	13000	2300	3230	3000	1880